

# RichTextEditor TinyMCE configuration

---



[Ken Domen](#) 300 posts since

Sep 28, 2007

this is probably super simple.

what's the preferred way to configure tinyMCE in Clearspace.

our customers what the table stuff taken out of the RTE.

thanks!

Tags: [tinymce](#), [rte](#)



[Ken Domen](#) 300 posts since

Sep 28, 2007 1. **Re: RichTextEditor TinyMCE configuration** May 30, 2008 9:04 AM

This seems like the way to take out a table in the RTE.

1. copied guieditor.js to jiveHome/resources/script
2. took out **table** in that file:

**before:**

```
else if (_jive_tables_enabled) {
    guieditorplugins = "jiveemoticons,jivespell,paste,table,jivelink,jiveimage";
    guieditorvalidelements = "+code[class],+a[style|name|href|target|title|class],-strong/-
b[class|style],-em/-i[class|style],-strike[class|style],-u[class|style],+p[style|dir|class|align],-
ol[class|style],-ul[class|style],-li[class|style],br[clear],img[style|class|src|border|alt|=|title
hspace|vspace|width|height|align|id],-sub[style|class],-sup[style|class],-blockquote[style],-
div[class|align|style],-span[style|class|align],-pre[class|align|style],address[class|align|style],-
h1[style|class|align],-h2[style|class|align],-h3[style|class|align],-h4[style|class|align],-h5[style|
class|align],-h6[style|class|align],hr[class|style],-font[face|size|style|class|color],dd[class|
```

```
title|style|lang],dl[class|title|style|lang],dt[class|title|style|lang],-table[border:1|class:jive-wiki-table],-tr,tbody,thead,tfoot,#td,#th";  
    guieditorbuttons = "tablecontrols,separator";  
}
```

**after:**

```
else if (_jive_tables_enabled) {  
    guieditorplugins = "jiveemoticons,jivespell,pastejivelink,jiveimage";  
    guieditorvalidelements = "+code[class],+a[style|name|href|target|title|class],-strong/-b[class|style],-em/-i[class|style],-strike[class|style],-u[class|style],+p[style|dir|class|align],-ol[class|style],-ul[class|style],-li[class|style],br[clear],img[style|class|src|border|alt|=|title|hspace|vspace|width|height|align|id],-sub[style|class],-sup[style|class],-blockquote[style],-div[class|align|style],-span[style|class|align],-pre[class|align|style],address[class|align|style],-h1[style|class|align],-h2[style|class|align],-h3[style|class|align],-h4[style|class|align],-h5[style|class|align],-h6[style|class|align],hr[class|style],-font[face|size|style|class|color],dd[class|title|style|lang],dl[class|title|style|lang],dt[class|title|style|lang],-table[border:1|class:jive-wiki-table],-tr,tbody,thead,tfoot,#td,#th";  
    guieditorbuttons = "tablecontrols";  
}
```

And the table is gone.

I think a cooler way would be for us to figure out where **\_jive\_tables\_enabled** is and set that in the config somewhere.

thanks!

ken

**Attachments:**

## RichTextEditor TinyMCE configuration



[rte\\_table\\_take\\_out.png](#) (271.4 K)